



| REVISION | DATE | DESCRIPTION |
|----------|----------|---------------------------------|
| H | 18.11.08 | TYPICAL FLOOR DETAILS REFERENCE |

| | | |
|--------------------------------|----------------|-----|
| AUDI WEST LONDON LONDON, UK | DATE: NOV/08 | 1.4 |
| | SCALE: 1/50@A1 | |

CONSTRUCTION

| | |
|------------------|-----|
| DATE: NOV 08 | 1.4 |
| SCALE: 1/50 @ A1 | |

| | |
|---|--|
| General pavements: | |
| PAV 1 | Solus Ceramics, ALU/GM/G50 Anthracite Bright, 300x600 mm, R9 slip rating. |
| PAV 2 | 15 mm painted parquet, bergamot-parquet ash Technograu Trend-Epoca 2400x140x15 mm, glued installation with Skadbond-15x. |
| PAV 3 | Solus Ceramics, Aliai ZCPDP809, Ofi White, 100x100 mm. |
| General walls: | |
| EWL 1 | Glazed Breitwedge -laminated (extra clear-tinted) glass. (OMITTED) |
| EWL 2 | Acoustic laminated safety glass. |
| EWL 3 | 12.5 mm double layer of standard plasterboard painted white RAL 9010. |
| EWL 4 | 12.5 mm sound resistant double layer of plasterboard painted white RAL 9010. |
| EWL 5 | 12.5 mm moisture resisting double layer of plasterboard painted white RAL 9010. |
| EWL 6 | Solus Ceramics, Aliai ZCPDP809, Ofi White, 100x100 mm. |
| EWL 7 | 12.5 mm moisture resisting double layer of plasterboard. |
| Wall coverings to define | |
| EWL 8 | 12.5 mm sound resistant double layer of plasterboard. |
| EWL 9 | 30 mm Kermitic duct panel, Noxx TR, white 9095. |
| IWL 1 | 70 mm Lightweight metal stud at 600 mm centers. |
| IWL 2 | 70 mm Lightweight metal stud at 600 mm centers. |
| IWL 3 | 67mm Acoustic partition slab between studs. |
| IWL 4 | 50 mm Lightweight metal stud at 600 mm centers. |
| IWL 5 | 50 mm Lightweight metal stud at 600 mm centers. |
| IWL 6 | 47mm Acoustic partition slab between studs. |
| IWL 7 | 90 mm Lightweight metal stud at 600 mm centers. |
| IWL 8 | 67mm Acoustic partition slab between studs. |
| General ceilings: | |
| CEI 1 - 2ND FLOOR | |
| Suspended ceilings system: | |
| Standard plasterboard painted white RAL 9010. | |
| CEI 1 - 3RD FLOOR | |
| Suspended ceilings system: | |
| 12.5 mm double layer of standard plasterboard painted white RAL 9010. | |
| CEI 2 | |
| Suspended ceilings system: | |
| Moisture resisting plasterboard painted white RAL 9010. | |
| CEI 3 | |
| Suspended ceilings system: | |
| Plasterboard painted white RAL 9010 (Sound resistant double layers of 12.5 mm each side). | |
| 100 mm Acoustic partition slab between light steel joists. | |
| CEI 4 | |
| Ceiling tiles 600x600x15 mm, Rockfon Pacific® range, E edge detail. | |
| CEI 5 | |
| Metal suspended ceiling 900x250x30 mm, SAS Translucel. | |
| Polyester powder coated in standard range White RAL 9010. | |
| # Separation between ceramic tiles and parquet flooring with Schlüter - SCHIENE, stainless steel. | |
| # Movement joints with Schlüter ® - DILEX EKSU, movement zone on synthetic rubber. | |
| # All visible steel plates coated in white RAL 9010. | |