

**General information**

Finish to ironmongery: if not indicated otherwise to be brushed or satin stainless steel

Fire doors to be provided with intumescent smoke seals rebated into sides and top of door – type to be agreed.

Provide test cylinder only – cylinders to be supplied / replaced by client

Notices other than fire door etc TBC

**Door(s) DC01**

Description: top hung end fold bi-parting sliding folding timber doors

Purpose: cupboard doors to hide sink / shelves in education room 2

Frame: bespoke softwood frame to suit.

Door leaf: 31mm lipped solid core door

Spec ref: L20/540

Drawing ref: 332-A-506 rev E

Ironmongery:

quantity	generic description	product ref
1	Rosette	Hafele 219.27.686
1	18mm Cylinder - Key to Differ	Hafele 230.22.602
1	Shutter Lock Case Only	Hafele 230.37.201
2	Door gear as L20/540	Assumed fitted on site
3	Knob Slide Action Bolt - Satin Nickel Plate	Hafele 900.17.946
4	65mm Dia.Flush Pull Handle Sat. St. Steel	Hafele 902.00.520
2	Channel as L20/540	Assumed fitted on site
2	Track as L20/540	Assumed fitted on site

**Door(s) DC02**

Description: pair of side hung flush timber doors

Purpose: cupboard doors to hide manifold in education room

Frame: bespoke softwood frame to suit, min 38 x 100mm softwood with 12 x 38mm stops

Door leaf: 44mm flush door; plain meeting stiles

Spec ref: L20/412 (non-fire rated)

Drawing ref: 332-A-506 rev E

Ironmongery:

quantity	generic description	product ref
4	100mm stainless steel butt hinges	Allgood SS8066CB
2	Rebated flush bolts, top and bottom, to slave leaf	Allgood SS48800
1	Floor socket	Allgood SC7051
2	65mm Dia.Flush Pull Handle Sat. St. Steel	Hafele 902.00.520
1no	Brass mortised roller catch (master leaf)	Contractor's choice
1no	Mortise dead lock (master leaf) and keep (slave leaf) for eurocylinder – case only	Allgood SS7186F60
1no	Escutcheon	Allgood SS83435S21

**Door(s) DC03**

Purpose: cupboard doors to hide manifold in education room

Matches door DC02 in all respects.

**Door(s) DC04**

Description: pair of side hung flush timber doors

Purpose: cupboard doors to AV cupboard in store room H

Frame: bespoke softwood frame to suit, min 38 x 100mm softwood with 12 x 38mm stops

Door leaf: 44mm flush door; plain meeting stiles

Spec ref: L20/413 (30FDS)

Drawing ref: 332-A-1001 rev B

Ironmongery:

quantity	generic description	product ref
6	100mm stainless steel butt hinges	Allgood SS8066CB
6	Intumescent packs for hinges	Allgood XX8066FP
2	Rebated flush bolts, top and bottom, to slave leaf	Allgood SS48800
1	Floor socket	Allgood SC7051
2	Intumescent pack for flush bolt	Allgood 48800FP
2	200mm 19 dia pull handle	Allgood SS84214S20
4	Galvanised steel bush for secret face fixing	Allgood SS84955S30
1no	Brass mortised roller catch (master leaf)	Contractor's choice
1no	Mortise dead lock (master leaf) and keep (slave leaf) for eurocylinder – case only	Allgood SS7186F60
1no	Escutcheon	Allgood SS83435S21
1no	Intumescent sleeve for mortise lock	Allgood XX7176FP60
1no	76mm dia fire door keep shut notice	Allgood SS8448
4 no	Intumescent louvres	L20/413

**Door(s) DC05**

Description: top hung sliding timber doors

Purpose: cupboard doors for cleaner's cupboard

Frame: bespoke softwood frame to suit.

Door leaf: 31mm lipped solid core door

Spec ref: L20/540

Drawing ref: 332-A-507 rev D

Ironmongery:

quantity	generic description	product ref
1	Door gear	Assumed fitted on site
2	65mm Dia.Flush Pull Handle Sat. St. Steel	Hafele 902.00.520
2	3/L Mortice Clawbolt Deadlock - Sat. St. Steel	Hafele 911.26.155

**Door(s) DC06**

Description: sliding folding doors

Purpose: cupboard doors to education 2 sink and shelves

Frame: bespoke softwood frame to suit, min 38 x 100mm softwood

Door leaf: 31mm lipped solid core door

Spec ref: L20/412 (non-fire rated)

Drawing ref: 332-A-507 – rev C

Ironmongery:

quantity	generic description	Product ref
1	Rosette	Hafele 219.27.686
1	18mm Cylinder - Key to Differ	Hafele 230.22.602
1	Shutter Lock Case Only	Hafele 230.37.201
1	Sliding door gear	Assumed fitted on site
1	Sliding door gear guide	Assumed fitted on site
1	Knob Slide Action Bolt - Satin Nickel Plate	Hafele 900.17.946
2	65mm Dia.Flush Pull Handle Sat. St. Steel	Hafele 902.00.520
12	hinges	Assumed fitted on site
1	channel	Assumed fitted on site

1	track	Assumed fitted on site
---	-------	------------------------

**Door(s) DC07**

Description: pair of side hung flush timber doors

Purpose: cupboard doors to AV/IT cupboard to G

Frame: bespoke softwood frame to suit, min 38 x 100mm softwood with 12 x 38mm stops

Door leaf: 44mm flush door; plain meeting stiles

Spec ref: L20/413 (30FDS)

Drawing ref: 332-A-508 rev C

Ironmongery:

quantity	generic description	product ref
6	100mm stainless steel butt hinges	Allgood SS8066CB
6	Intumescent packs for hinges	Allgood XX8066FP
2	Rebated flush bolts, top and bottom, to slave leaf	Allgood SS48800
1	Floor socket	Allgood SC7051
2	Intumescent pack for flush bolt	Allgood 48800FP
2	200mm 19 dia pull handle	Allgood SS84214S20
4	Galvanised steel bush for secret face fixing	Allgood SS84955S30
1no	Brass mortised roller catch (master leaf)	Contractor's choice
1no	Mortise dead lock (master leaf) and keep (slave leaf) for eurocylinder – case only	Allgood SS7186F60
1no	Escutcheon	Allgood SS83435S21
1no	Intumescent sleeve for mortise lock	Allgood XX7176FP60
1no	76mm dia fire door keep shut notice	Allgood SS8448
4 no	Intumescent louvres	L20/413

**Door(s) DC08**

Purpose: cupboard doors to AV/IT cupboard to G

Matches door DC07 in all respects **except no louvres**.**Door(s) DC09**

Description: pair of side hung flush timber doors

Purpose: cupboard doors to batteries in plant room E

Frame: bespoke softwood frame to suit, min 38 x 100mm softwood with 12 x 38mm stops

Door leaf: 44mm flush door; plain meeting stiles

Spec ref: L20/414 (60FDS)

Drawing ref: amended drawing to follow

Ironmongery matches Door(s) DC07 **except no louvres****Door(s) DC10**

Description: single side hung flush timber door

Purpose: cupboard doors to hide distribution board in education room 2

Frame: bespoke softwood frame to suit, min 38 x 100mm softwood with 12 x 38mm stops

Door leaf: 44mm flush door; plain meeting stiles

Spec ref: L20/412 (non-fire rated)

Drawing ref: 332-A-507 rev D

Ironmongery:

quantity	generic description	product ref
2	100mm stainless steel butt hinges	Allgood SS8066CB
2	65mm Dia.Flush Pull Handle Sat. St. Steel	Hafele 902.00.520
1no	Brass mortised roller catch (master leaf)	Contractor's choice
1no	Mortise dead lock (master leaf) and keep (slave leaf) for eurocylinder – case only	Allgood SS7186F60
1no	Escutcheon	Allgood SS83435S21