



## Hardware Schedule

Ian Andrews  
Raphael Contracting Ltd  
Hi-Tec House  
Roebuck Road  
Chessington  
Surrey  
KT9 1EU  
Re: Gloucester Quays  
Gloucester

Date: 26 January 2009  
Quote No: 1352-00  
Quote Ref: Pillar and Lucy House  
  
Your Ref:  
  
Estimator: Ashley Burbery  
Rep: Ashley Burbery

---

New schedule created by Ashley Burbery Dip G.A.I. 15th October 2007

Door schedule used DY-SCH-(32)7-99-501 Revisopn 2

Revised 28th October 2008:

- 1, Door closers changed from 44008 type to 41008
- 2, Intumescent for locks and hinges added

Revised 26th January 2009:

- 1, Track, pivots and hinges added for 'Pivette' type doors



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 01

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ12138AA	SSS sashlock case with radiused forend and strike plate, spindle grip follower, 60mm backset and 72mm centres	1	Each
371	SCP 70mm euro profile 6 pin cylinder and oval thumb turn to registered patent protected master key system with multi profile keyways, tested to PR EN 1634/1 and exceeding CEN 1303 grade 5	1	Each
12191	SSS 19mm diameter safety lever handle on 50x4mm round concealed fixing unsprung rose with a bronze self lubricating washer and with bolt through and spindle fast fixing. Dimensions comply with BS8300 Doc M	1	Set
19004	SSS 52x4mm concealed fixed europrofile cylinder escutcheon	2	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
2		Doors	

### Door References

B.D.06                      B.D.07



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 03

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
ZZ11911AA	200x200x0.5mm FD60 lock intumescent	1	Each
ZZ12138AA	SSS sashlock case with radiused forend and strike plate, spindle grip follower, 60mm backset and 72mm centres	1	Each
371	SCP 70mm euro profile 6 pin cylinder and oval thumb turn to registered patent protected master key system with multi profile keyways, tested to PR EN 1634/1 and exceeding CEN 1303 grade 5	1	Each
12191	SSS 19mm diameter safety lever handle on 50x4mm round concealed fixing unsprung rose with a bronze self lubricating washer and with bolt through and spindle fast fixing. Dimensions comply with BS8300 Doc M	1	Set
19004	SSS 52x4mm concealed fixed europrofile cylinder escutcheon	2	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	2	Each
<b>6 Doors</b>			

### Door References

0.D.10	0.D.11	1.D.12	2.D.12
3.D.12	4.D.11		



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 04

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
ZZ11911AA	200x200x0.5mm FD60 lock intumescent	1	Each
ZZ12139AA	SSS deadlock case with radiused forend / strike plate and 60mm backset	1	Each
373	SCP 40mm euro profile 6 pin single cylinder to registered patent protected master key system with multi profile keyways, tested to PR EN 1634/1 and exceeding CEN 1303 grade 5	1	Each
60014	SSS euro profile cylinder pull	1	Each
60405B	SSS 75mm diameter sign to read Fire Door Keep Locked	1	Each

**4 Doors**

### Door References

0.D.13	0.D.14	3.D.14	3.D.15
--------	--------	--------	--------



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 05

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
ZZ11911AA	200x200x0.5mm FD60 lock intumescent	1	Each
ZZ12139AA	SSS deadlock case with radiused forend / strike plate and 60mm backset	1	Each
371	SCP 70mm euro profile 6 pin cylinder and oval thumb turn to registered patent protected master key system with multi profile keyways, tested to PR EN 1634/1 and exceeding CEN 1303 grade 5	1	Each
ZZ11962	SSS T Bar style pull handle 900x19mm complete with bolt through fixings	1	Each
	1000x80x1.5mm push plate with radiused corner	1	Each
19004	SSS 52x4mm concealed fixed europrofile cylinder escutcheon	2	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	2	Each

### 8 Doors

#### Door References

1.D.06	1.D.11	2.D.06	2.D.11
3.D.11	3.D.16	4.D.09	4.D.10



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 06

Product	Description	Quantity	Unit
026654	Carrier plate for double roller	1	Each
055778	Double roller with suspension bolt for 80kg doors	1	Each
069991	Ceiling mounting plates for track	1	Each
120151	1650mm sliding door track for 80kg doors	1	Each
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
20014	SSS double action pivot set suitable for doors upto 150kg with fully adjustable top centre and with pin retraction	1	Set
ZZ12140AA	SSS bathroom lock with radiused forend and strike plate, spindle grip follower, 60mm backset and 78mm centres	1	Each
12191	SSS 19mm diameter safety lever handle on 50x4mm round concealed fixing unsprung rose with a bronze self lubricating washer and with bolt through and spindle fast fixing. Dimensions comply with BS8300 Doc M	1	Set
11114	5-8mm alum conversion sleeve	1	Each
19007	SSS 52x4mm concealed fixed large bathroom thumbturn and release with indicator	1	Each
	SSS 450x150x1.2mm kicking plate (nominal size)	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each

### 3 Doors

#### Door References

1.D.07                      2.D.07                      3.D.07



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 07

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ12140AA	SSS bathroom lock with radiused forend and strike plate, spindle grip follower, 60mm backset and 78mm centres	1	Each
12191	SSS 19mm diameter safety lever handle on 50x4mm round concealed fixing unsprung rose with a bronze self lubricating washer and with bolt through and spindle fast fixing. Dimensions comply with BS8300 Doc M	1	Set
11114	5-8mm alum conversion sleeve	1	Each
19007	SSS 52x4mm concealed fixed large bathroom thumbturn and release with indicator	1	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
41011	SSS figure 6 mounting bracket for 41000 series door closers	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each

### 3 Doors

#### Door References

1.D.08	2.D.08	3.D.08
--------	--------	--------



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 08

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ12140AA	SSS bathroom lock with radiused forend and strike plate, spindle grip follower, 60mm backset and 78mm centres	1	Each
12191	SSS 19mm diameter safety lever handle on 50x4mm round concealed fixing unsprung rose with a bronze self lubricating washer and with bolt through and spindle fast fixing. Dimensions comply with BS8300 Doc M	1	Set
11114	5-8mm alum conversion sleeve	1	Each
19007	SSS 52x4mm concealed fixed large bathroom thumbturn and release with indicator	1	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each

### 7 Doors

#### Door References

1.D.09	1.D.10	2.D.09	2.D.10
3.D.09	3.D.10	4.D.08	





## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 09

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
ZZ11911AA	200x200x0.5mm FD60 lock intumescent	1	Each
ZZ12138AA	SSS sashlock case with radiused forend and strike plate, spindle grip follower, 60mm backset and 72mm centres	1	Each
371	SCP 70mm euro profile 6 pin cylinder and oval thumb turn to registered patent protected master key system with multi profile keyways, tested to PR EN 1634/1 and exceeding CEN 1303 grade 5	1	Each
12191	SSS 19mm diameter safety lever handle on 50x4mm round concealed fixing unsprung rose with a bronze self lubricating washer and with bolt through and spindle fast fixing. Dimensions comply with BS8300 Doc M	1	Set
19004	SSS 52x4mm concealed fixed europrofile cylinder escutcheon	2	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
41011	SSS figure 6 mounting bracket for 41000 series door closers	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	2	Each

### 6 Doors

#### Door References

1.D.16	1.D.17	2.D.16	2.D.17
3.D.17	3.D.18		



## Hardware Schedule

**Re: Gloucester Quays**



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 10

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	3	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	12	Each
ZZ11962	SSS T Bar style pull handle 900x19mm complete with bolt through fixings	2	Each
	1000x80x1.5mm push plate with radiused corner	2	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	2	Each
	SSS 450x150x1.2mm kicking plate (nominal size)	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	2	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	4	Each

---

### 3 Doors

---

#### Door References

---

1.D.20	2.D.20	3.D.21
--------	--------	--------



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 11

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
51101C	SSS single certifire and CE marked heavy duty touch bar panic latch with deadlocking stainless steel latch bolt and hex key hold back to BS EN11125 suitable for doors 585 - 915mm wide	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	2	Each
60429	Rigid plastic 600x100mm sign white on green to read Push Bar To Open	1	Each
60429	Rigid plastic 80x80mm sign to read Fire Escape Keep Clear	1	Each

**4 Doors**

### Door References

1.D.25	2.D.25	3.D.26	4.D.12
--------	--------	--------	--------



## Hardware Schedule

Re: Gloucester Quays

Hardware Set Ref: 12

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
ZZ11911AA	200x200x0.5mm FD60 lock intumescent	1	Each
ZZ12139AA	SSS deadlock case with radiused forend / strike plate and 60mm backset	1	Each
371	SCP 70mm euro profile 6 pin cylinder and oval thumb turn to registered patent protected master key system with multi profile keyways, tested to PR EN 1634/1 and exceeding CEN 1303 grade 5	1	Each
ZZ11962	SSS T Bar style pull handle 900x19mm complete with bolt through fixings	1	Each
	1000x80x1.5mm push plate with radiused corner	1	Each
19004	SSS 52x4mm concealed fixed europrofile cylinder escutcheon	2	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	2	Each
70001M	SE 12/24V dc single monitored slimline electro magnetic lock	1	Each

## 2 Doors

### Door References

3.D.06 3.D.13

## Hardware Schedule

**Re: Gloucester Quays**

**Hardware Set Ref: 13**

Product	Description	Quantity	Unit
20006R	SSS 102x76x2.5mm shrouded ball bearing hinge for doors upto 120kg to BS EN1935 grade 13 and BS EN1634 FD60 with radius corners	1.5	Pair
ZZ11910AA	100x30x0.5mm FD60 hinge intumescent pad	6	Each
ZZ11962	SSS T Bar style pull handle 900x19mm complete with bolt through fixings	1	Each
	1000x80x1.5mm push plate with radiused corner	1	Each
41008	SSS adjustable power EN1154 2-4 Certifire approved overhead door closer with self adjusting backcheck and adjustable closing speed by two valves complete with full square cover and matching armset	1	Each
	SSS 900x150x1.2mm kicing plate (nominal size)	1	Each
60031	SSS shielded floor mounted door stop with locating pin	1	Each
60406B	SSS 75mm diameter sign to read Fire Door Keep Shut	2	Each
		<b>1</b>	<b>Doors</b>

## Door References

4.D.03



## Hardware Schedule

Re: Gloucester Quays

### Door Summary

Door Ref.	Set Ref.						
0.D.10	03	0.D.11	03	0.D.13	04	0.D.14	04
1.D.06	05	1.D.07	06	1.D.08	07	1.D.09	08
1.D.10	08	1.D.11	05	1.D.12	03	1.D.16	09
1.D.17	09	1.D.20	10	1.D.25	11	2.D.06	05
2.D.07	06	2.D.08	07	2.D.09	08	2.D.10	08
2.D.11	05	2.D.12	03	2.D.16	09	2.D.17	09
2.D.20	10	2.D.25	11	3.D.06	12	3.D.07	06
3.D.08	07	3.D.09	08	3.D.10	08	3.D.11	05
3.D.12	03	3.D.13	12	3.D.14	04	3.D.15	04
3.D.16	05	3.D.17	09	3.D.18	09	3.D.21	10
3.D.26	11	4.D.03	13	4.D.08	08	4.D.09	05
4.D.10	05	4.D.11	03	4.D.12	11	B.D.06	01
B.D.07	01						



## Hardware Schedule

Re: Gloucester Quays

### Set Summary

Set Ref.	Door Qty
01	2
03	6
04	4
05	8
06	3
07	3
08	7
09	6
10	3
11	4
12	2
13	1
<hr/>	
Total Doors: 49	





## Hardware Schedule

**Re: Gloucester Quays**